

# PRODUCT DATASHEET CA13636\_G2-LAURA-R-XW-P

### **G2-LAURA-R-XW-P**

Mini reflector with  $\sim$ 72° wide beam. Assembly with thinner white holder, installation tape and location pins.

#### **TECHNICAL SPECIFICATIONS:**

Dimensions 21.6 mm
Height 13.1 mm
Fastening tape, pin
Colour white

Box size 451 x 254 x 152 mm

Box weight 3.4 kg

Quantity in Box 1440 pcs


ROHS compliant yes 

(1)



#### **MATERIAL SPECIFICATIONS:**

	mponent	Туре	Material	Colour
LAU	JRA-R-XW	Reflector	HRPC	white
LAU	JRA-LT-PIN-XP-HLD-WHT	Holder	PC	white
RO	SE-TAPE	Tape	PU tape	black
LAU	JRA-LT-PIN-XP-HLD-WHT	Holder	PC	wh



# PRODUCT DATASHEET CA13636\_G2-LAURA-R-XW-P

## PHOTOMETRIC DATA (MEASURED):

# CREE 💠

LED XP-E

**FWHM** 


71.0°

Efficiency

84 %

Peak intensity 0.700 cd/lm Required components:





# CREE ÷

LED

XP-E2

**FWHM** 

74.0°


Efficiency

86 %

Peak intensity 0.630 cd/lm

Required components:





# CREE \$

LED

XP-G

**FWHM** 

72.0°

Efficiency

86 %

Peak intensity 0.590 cd/lm

Required components:

# CREE 💠

LED

XP-G2

**FWHM** 

71.0°


Efficiency

87 %


Peak intensity 0.760 cd/lm

Required components:





### PHOTOMETRIC DATA (MEASURED):



## PHOTOMETRIC DATA (MEASURED):

### **WNICHIA**

LED NVSxx19A


**FWHM** 75.0° Efficiency

81 %

Peak intensity 0.560 cd/lm

Required components:





### **WNICHIA**

LED NVSxx19B/NVSxx19C

**FWHM** 70.0° Efficiency 79 %

Peak intensity 0.700 cd/lm

Required components:




# OSRAM Opto Semiconductors


LED Oslon Square EC

**FWHM** 70.0° Efficiency 84 % Peak intensity 0.720 cd/lm Required components:





# PHOTOMETRIC DATA (SIMULATED):



#### **GENERAL INFORMATION:**

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

#### **MATERIALS:**

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

#### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### **LEDIL Oy**

Joensuunkatu 13 FI-24240 SALO Finland

#### LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

# Local sales and technical support

www.ledil.com/ where\_to\_buy

#### **Shipping locations**

Salo, Finland Hong Kong, China

#### **Distribution Partners**

www.ledil.com/ where\_to\_buy