


Adjustable Laser

VLM-635/650-02 Series



FEATURES:


- Industrial Red Dot Laser.
- Adjustable focus (**Focus range 100mm ~ Infinity**) Laser module with APC Driver Circuit inside, ideal for industrial Laser application.
- This module has integrated optic, laser diode, and APC driver circuit.
- APC Driver Circuit enables the Laser output power safe and constant.
- Includes patented solid brass structure for the best shock resistance and better heat transfer consideration.
- Aspherical plastic lens provides Dot Laser.
- Dimensions : $\Phi 10.5 \times 26$ mm ($\Phi 0.413" \times 1.023"$)
- Wavelength : 635 / 650 nm
- Output power : Class II – less than 1mW / Class IIIa – less than 5mW.
- Beam Divergence (Half Angle) : 0.5 mRad
- 2.6~5 VDC operation.
- Connection type: Lead wire / Spring.

APPLICATIONS:

- Industrial Red Dot Laser - Adjustable focus function. Ideal for Industrial positioning, measuring, pointing which would need an focusable beam at specific distances.
- Wood processing.
- Metal processing.
- Stone processing.
- Textile industry.
- Food industry.
- Automotive industry.
- Medical science

VLM-635/650-02 Series

OUTLINE DIMENSIONS (UNITS: mm)



SPECIFICATIONS

SPECIFICATIONS		635-02	650-02
1	Dimensions	$\phi 10.5 \times 26$ mm ($\phi 0.413" \times 1.023"$)	
2	Operating voltage (Vop)	2.6~5 VDC	
3	Operating current (Iop)	< 50mA	< 35mA
4	Continuous wave output power (Po)	LPT<1mW / LPA \leq 3mW	
5	Wavelength at peak emission (λ_p)	630~645nm	645~665nm
6	Collimating lens	Aspherical plastic lens($\phi 7$)	
7	Focus Range	100mm ~ Infinity	
8	Spot size at 5M	5 \pm 1 mm	
9	Divergence (Half Angle)	0.5 mrad	
10	Operating temp. range	+10°C ~+40°C	
11	Storage temp. range	-20°C ~+65°C	
12	Housing	Brass	
13	Mean time to failure (MTTF) 25°C	5000hrs	10000hrs

Note : Laser module housing is an electrical positive surface, it is imperative that contact between the laser module and the machine be avoided. This is to prevent damage from the machine electrical leakage. Surge protected power supply to the laser module is strongly recommended.

VLM-635/650-02 Series

ORDER CODE

Order Code	Wavelength	Output Power	Connection Type
VLM-635-02 LPA	635 nm	$\leq 3\text{mW}$	Lead Wire
VLM-635-02 LPT	635 nm	$< 1\text{mW}$	Lead Wire
VLM-635-02 SPA	635 nm	$\leq 3\text{mW}$	Spring
VLM-635-02 SPT	635 nm	$< 1\text{mW}$	Spring
VLM-650-02 LPA	650 nm	$\leq 3\text{mW}$	Lead Wire
VLM-650-02 LPT	650 nm	$< 1\text{mW}$	Lead Wire
VLM-650-02 SPA	650 nm	$\leq 3\text{mW}$	Spring
VLM-650-02 SPT	650 nm	$< 1\text{mW}$	Spring

SAFETY LABEL

