

General ordering data	
Order No.	0478260000
Part designation	AST 1 6.3/2.8
Version	Special terminal, special connections, 2.5 mm ² ,
	Flat-blade connection, Polyamide, beige, TS 32
EAN	4008190003043
Qty.	50 pc(s).
Product notes	
Note, technical data	Cable-lug connections should be fitted with insulating sleeves. 20 A with F 6.3 or 2 x F 2.8
Additional technical data	
Colour of insulating material	beige
Connection direction	top
End plate required	Yes
Explosion-tested version "Ex e"	No
Installation advice	TS 32
Insulating material	Polyamide
Levels cross-connected internally	No
No. of identical terminals	1
No. of levels	1
No. of terminal strips per level	4
Open sides	right
Operating temperature range	- 50 °C, + 100 °C
Product family	SAK Series
Type of connection	Plugged
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	V2
Version	Feed-through terminal
CSA rating data	
Voltage (CSA)	300 V
CSA current	16 A
Conductors for clamping (additional	
No. of connections	4
Conductors for clamping (rated connection)	
Clamping range, min.	0.5 mm²



Conductors for clamping (rated connection)	
Clamping range, max.	2.5 mm ²
Type of connection	Flat-blade connection
Connection direction	top
No. of connections	4
Flexible, min.	0.5 mm ²
Flexible, max.	2.5 mm ²
, -	
Dimensions	
Width	6.5 mm
Height of lowest version	46 mm
Length	58 mm
Weight	11.96 g
TS 32 offset	26 mm
Other connections	
Cable-lug connection	Slotted
No. of connections	4
Rated cross-section spade connector 2.8 mm	1 mm ²
Rated cross-section spade connector 6.3 mm	2.5 mm ²
Rating data	
Rated cross-section	2.5 mm ²
Rated voltage	500 V
Rated impulse voltage	6 kV
Rated current	20 A
Standards	IEC 60947-7-1 / IEC 61210
Current with max. conductor	20 A
Pollution severity	3
UL rating data	
Voltage (UL)	600 V
Current (UL)	13 A

Approvals

Approvals institutes



Classifications	
ETIM 2.0	EC000897
ETIM 3.0	EC000897
eClass 4.1	27-14-11-31
eClass 5.0	27-14-11-31
eClass 5.1	27-14-11-31

Weidmüller 🗲

Similar products

0266360000	AGT 163	Special terminal, special connections, 2.5 mm ² , Flat-blade
0200300000	A31 1 0.3	
		connection Delvemide being TS 22
		connection, Polyamide, beige, TS 32

