

## Part Number: 6400FC



## Security & Sound, 2 Conductor 20 AWG BC, Shielded, Plenum

## **Product Description**

Security & Sound Cable, 2 Conductor 20 AWG stranded (7x28) bare copper conductors with FEP insulation, Beldfoil® shield, Plenum, Flamarrest® jacket with ripcord.

## **Technical Specifications**

## **Product Overview**

Environmental Space:	Indoor - Plenum
Suitable Applications:	Pro Audio, Intercom/PA Systems, Security Systems

## **Physical Characteristics (Overall)**

## Conductor

AWG	Stranding	Material	No. of Conductors
20	7x28	BC - Bare Copper	2
Conductor Count:			
Condu	Conductor Size:		

## Insulation

Material	Nominal Wall Thickness
FEP - Fluorinated Ethylene Propylene	0.006 in

## Color Chart

Number	Color
1	Black
2	Red

## **Outer Shield Material**

Туре	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum/Polyester	Beldfoil®	100 %	TC - Tinned Copper	22	7x30 mm

## **Outer Jacket Material**

Material	Material Trade Name	Nominal Diameter	Nominal Wall Thickness	Ripcord
LS PVC - Low Smoke Polyvinyl Chloride	Flamarrest®	0.133 in	0.0165 in	Yes

## **Electrical Characteristics**

## Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
10.2 Ohm/1000ft	11.3 Ohm/1000ft

## Capacitance

Nom. Capacitance Conductor to Conductor Nom. Capacita		nce Conductor to Other Conductor to Shield
52 pF/ft	93.6 pF/ft	
Shielding:		Multiple or Specialty

## Inductance

Nominal Inductance 0.15 µH/ft

#### Current

# Max. Recommended Current [A] 3.75 Amps per conductor @ 25°C A

## Voltage



## **Temperature Range**

UL Temp Rating:	75°C
Operating Temp Range:	0°C To +75°C

## **Mechanical Characteristics**

Bulk Cable Weight:	13.6 lbs/1000ft
Max Recommended Pulling Tension:	37.1 lbs
Min Bend Radius/Minor Axis:	1.3 in

## **Standards**

NEC Articles:	800
NEC/(UL) Specification:	CMP
CEC/C(UL) Specification:	CMP

## **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## Flammability, LS0H, Toxicity Testing

C(UL) Flammability:	FT6
UL Flammability:	NFPA 262 Plenum Flame Test (UL910)
UL voltage rating:	300 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	Yes	

## **Part Number**

## Variants

Item #	Color
6400FC 877U1000	Natural

## © 2018 Belden, Inc

## All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.