	1		2		3	4	5	
RoHS Compliant PROJECTION: GENERAL TOLERANCE K 05-DEC-14 LAYOUT+DISCL. AS J 01-SEP-14 DIMY/IEWS+UL AS J 01-SEP-14 DIMY/IEWS+UL AS H 08-NOV-11 CUUREINT RATING GG		PIN 5			RECOMMENDED PCB THIC	TECHNICAL CH MATERIAL INSULATOR MA FLAMMABILITY COLOR: BLACK CONTACT MATE CONTACT TYPE CONTACT TYPE CONTACT PLAT SHIELDING: BR QUALITY CLASS CONTACT PLAT SHIELDING: BR QUALITY CLASS ENVIRONMENT. OPERATING TE COMPLIANCE: I ELECTRICAL CURRENT RATI WORKING VOLT INSULATOR RE: DIELECTRIC WI CONTACT RESI STANDARD CERTIFIED: SOLDERING JEDEC LEAD FF PACKAGING	TERIAL: LCP RATING: UL94-V0 RIAL: COPPER ALLOY : STAMPED ING: SELECTIVE GOLD ASS WITH NI PLATING :: 1500 MATING CYCLES AL MPERATURE: -40 UP TO 105°C EAD FREE AND ROHS NG: 1.0 A MAX AGE: 30 VAC SISTANCE: >1000 MΩ THSTANDING VOLTAGE: 750 VAC/MIN STANCE: 20 mΩ MAX E323964	
Image: Scale in the image: scale in	RoHS Compliant							С
J 01-SEP-14 DIM.+VIEWS+UL AS APPROVAL: NPr UNIT: MM DESCRIPTION: WR-COM - VERTICAL MINI USB 2.0 TYPE B 5 CONTACTS SIZE D I 18-FEB-13 DESIGNATION AR SCALE: SCALE: A4 A4 H 08-NOV-11 CURRENT RATING GG SHEET: 1/2 WERI PART NO: 651 005 136 421 A4	К 05-DEC-14				.X = ⁺ /_ 0.2			\mathbb{P}
I 18-FEB-13 DESIGNATION AR H 08-NOV-11 CURRENT RATING GG SCALE: SHEET: 1/2 WERI PART NO: 651 005 136 421 A4				PPROVAL: NPr	UNIT: MM	DESCRIPTION: WR-COM - VERTICAL MINI	USB 2.0 TYPE B 5 CONTACTS SIZE	╔┤┍
]	A	-
	H 08-NOV-11 CU REV DATE	FILE	GG BY		SHEET: 1/2 DRAW: AS	WERI PART NO: 651 005 136 421		4

1	2	3	4	5	-
					_

А

В

С

Cautions and Warnings:

This electronic component is designed and developed with the intention for use

in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Wurth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.

R	toHS Compliant							
G				PROJECTION:	GENERAL TOLERANCE			1
F					.X = ⁺ /_ 0.2			
E					.XX = ⁺ /_ 0.15			
D						WÜRTH ELEKTRONĪK		
С				APPROVAL: JC	UNIT: MM	DESCRIPTION: DISCLAIMER	SIZE	ld
В]	SCALE:			٢
A	10-SEP-14	PDF	QL]	SHEET: 2/2	WERI PART NO: DISCLAIMER	A4	
REV	DATE	FILE	BY		DRAW: QL			