

## Crimping pliers - CRIMPFOX-RCI 6-1 - 1212059

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Crimping pliers, for insulated cable lugs, 0.5 mm<sup>2</sup> ... 6.0 mm<sup>2</sup> (red, blue, yellow), oval crimp, asymmetrical

### Why buy this product

- ✓ CRIMPFOX-RCI 6 /... represent the top end of the range for cable lug crimping pliers
- ✓ Precision-manufactured dies ensure consistently high levels of quality during contact processing



### Key Commercial Data

|              |   |
|--------------|---|
| Packing unit | 1 STK   |
| GTIN         | <br>4 046356 453967 |
| GTIN         | 4046356453967   |

### Technical data

#### Dimensions

|            |        |
|------------|--------|
| Length (b) | 256 mm |
| Width (a)  | 25 mm  |
| Height (c) | 68 mm  |

#### General

|                    |                      |
|--------------------|----------------------|
| Color              | black                |
| Compression        | Oval crimp           |
| Type of contact    | Insulated cable lugs |
| Designation        | Crimping position 1  |
| Min. cross section | 0.5 mm <sup>2</sup>  |
| Max. cross section | 1.5 mm <sup>2</sup>  |
| AWG min            | 20                   |
| AWG max            | 16                   |
| Designation        | Crimping position 2  |

# Crimping pliers - CRIMPFOX-RCI 6-1 - 1212059

## Technical data

### General

|                    |                     |
|--------------------|---------------------|
| Min. cross section | 1.5 mm <sup>2</sup> |
| Max. cross section | 2.5 mm <sup>2</sup> |
| AWG min            | 16                  |
| AWG max            | 14                  |
| Designation        | Crimping position 3 |
| Min. cross section | 4 mm <sup>2</sup>   |
| Max. cross section | 6 mm <sup>2</sup>   |
| AWG min            | 12                  |
| AWG max            | 10                  |
| Weight             | 578 g               |
| Min. cross section | 0.5 mm <sup>2</sup> |
| Max. cross section | 6 mm <sup>2</sup>   |

## Approvals

### Approvals

---

Approvals

EAC

---

Ex Approvals

---

### Approval details

|     |   |                          |
|-----|---|--------------------------|
| EAC |  | RU x-<br>DE.xx08.B.02974 |
|-----|---|--------------------------|

---

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>