

SERIES EG1380 SWITCHES



E-SWITCH™

SLIDE SWITCHES



FEATURES & BENEFITS

Tape & Reel Packaging
3-position
Surface Mount
Sub-miniature

APPLICATIONS / MARKETS

Computer Servers/peripherals
Consumer electronics
Instrumentation
Test & measurement

MECHANICAL SPECIFICATIONS

| | |
|------------------|---|
| Mechanical Life: | 10,000 cycles |
| Force: | 250 +/- 100 gf to center position 300 +/-150 gf from center position |
| Travel: | 2.0 +/- 0.1mm each position |

ELECTRICAL SPECIFICATIONS

| | |
|------------------------|----------------------|
| Electrical Life: | 10,000 cycles |
| Contact Rating: | 300mA @ 6VDC |
| Contact Resistance: | 70mΩ (initial max) |
| Insulation Resistance: | 100MΩ (Min @ 500VDC) |
| Dielectric Strength: | 500VAC |

ENVIRONMENTAL SPECIFICATIONS

| | |
|------------------------|----------------|
| Operating Temperature: | -10°C to +60°C |
| Storage Temperature: | -20°C to +70°C |

HOW TO ORDER:

SERIES

EG

MODEL

1380

ACTUATOR

A = 2.0mm

